

griptech

MOBILE WEIGHING | GT Multidrucker HD



Attachments

Weighing systems

Camera systems

Features:

- ▶ Compatible with all systems (except for the weighing hand pallet truck HPT)
- ▶ Temperature range: -18°C to +50°C
- ▶ Protection class: IP54
- ▶ Thermal printer
- ▶ Connection: Serial RS232 and USB (via USB to RS232 cable)

The robust thermal printer for your weighing systems

The GT Multidrucker HD thermal direct printer is the ideal solution for use with all Griptech weighing systems – with the exception of the weighing hand pallet truck HPT. Its rugged housing, vibration-damped mounting plate, and shock-resistant power supply ensure reliable print results even in demanding working environments.

The print width of 72 mm enables precise and clearly structured printouts. Designed for use under extreme conditions, the GT Multiprinter HD operates reliably within a temperature range of -18° to +50°C. With protection class IP54, the printer is also well-protected against dust and splashing water.

Technical Data:

- › Print speed: up to 5 in/sec (127 mm/sec)
- › Resolution: 203 dpi (8 dots/mm)
- › Printhead life: 50 km
- › Print width: up to 72 mm
- › Interface: Serial RS232 and USB (via USB to RS232 cable)
- › Optional interfaces: Bluetooth (4.0) or Wi-Fi (802.11 b/g/n)
- › Roll size: max. diameter 2.6" (6.6 cm), core diameter 0.75" (19 mm), width 2.26" to 3.125" (5.7 to 8.0 cm)
- › Roll length: approx. 52 m
- › Dimensions: 127 x 165 x 101 mm (W x D x H)
- › Weight: 0.73 kg
- › Input voltage: 9–32 V
- › Operating temperature: -18° to +50°C (printing); -20° to +60°C (storage)
- › Mean time between failures: 10,000 hours
- › Certifications: CE, FCC Class B, UL, E1
- › Protection class: IP54 acc. to IEC 529; withstands multiple drops from 1.8 m height acc. to IEC 68-2
- › Bluetooth (optional): Compatible Bluetooth 4.0 stack, protocols: L2CAP, RFCOMM, SDP; profiles: GAP, SDAP, SPP, BTLE
- › Wi-Fi: Encryption: WEP, WPA-PSK/TKIP, WPA2-AES, 802.1x EAP with TLS, TTLS, LEAP, FAST, PEAP