

griptech

RLED MONITOR | 7"



Attachments

Weighing systems

Camera systems

Features:

- ▶ Resolution WVGA 800 x RGB x 480 pixels
- ▶ Viewing angle: 70° horizontal, 60° vertical
- ▶ 7" TFT-LCD with LED backlight
- ▶ Response time: 5 ms
- ▶ Surface hard coating (3H) with AG LR (Low Reflection) polarizer

RLED MONITOR | 7"

7" standard monitor

The standard 7" RLED monitor (screen diagonal 175 mm) offers excellent image quality in combination with Orlaco cameras. As a high-performance model, this monitor has been specially developed for intensive and mobile applications.

Features:

- › Power supply: 12–60 Volts
- › 12 Watts at 24 Volts
- › Protection class IP67 according to IEC 60529
- › Operating temperature: -40° to +85°
- › Suitable for cold storage use without enclosed cabin
- › Robust aluminum/plastic housing
- › Over- and under-voltage protection
- › Shock and vibration resistant
- › Supports up to 4 cameras
- › 430,000 pixels (800 x RGB x 480)
- › Intuitive OSD menu in 15 languages
- › Digital detail enhancement
- › Light-diffusing coating to prevent reflections
- › Automatic backlight control via light sensor
- › Response time: 5 ms
- › Viewing angle: 70° horizontal, 60° vertical
- › All materials comply with the requirements of the Green Passport according to IMO Resolution MEPC.197(62) of July 15, 2011 (Maritime sector: International Maritime Organization concerning the functions of the Marine Environment Protection Committee)

